



ITEM NO.	PART NUMBER	DESCRIPTION	QTY.
1	1752160-1500L-60CONE	1500L 30DEG Cone tank	1
2	100 OM Slider adaptor flange	Adaptor flange - slider valve connection	1
3	100 OM Valve	100 OM Slider valve	1

DESIGN DATA	
TANK CONTENTS:	S.G.
DESIGN PRESSURE: ATMOSPHERIC	MAXIMUM CAPACITY (LTRS):
DESIGN TEMPERATURE: 40°C	WORKING CAPACITY (LTRS):
WORKING PRESSURE: ATMOSPHERIC	APPROX. WEIGHT FULL (KGS):
WORKING TEMPERATURE: 40°C	APPROX. WEIGHT EMPTY (KGS):
MOULDED LIFTING LUGS: 4 - 0°, 90°, 180° & 270°	
METHOD OF SUPPORT: FIRM, FLAT, FULLY SUPPORTING BASE OF CONCRETE OR OTHER SUITABLE MATEREAL	

MATERIAL DATA	
MATERIALS OF CONSTRUCTION:	COLOUR: Natural
MATRIX REVOLVE N-307. REVOLVE IS A HIGH DENSITY (0.939 g/cm3), LOW MELT (3.5 g/ 10 min) HEXENE POLYETHYLENE GRADE FOR ROTOMOULDING. THE GRADE IS FULLY PROTECTED AGAINST THERMAL AND LIGHT DEGRADATION: N-307 IS UV10 STABILISED.	

INSPECTION AND TESTING
WORKS TEST: ALL TANKS ARE THICKNESS TESTED BY ULTRASOUND AFTER DEMOULD IN ADDITION AIR SUPPORTED LEAK TEST ARE CARRIED OUT ON FLANGE LINES.

NOTE SECTION

	NAME	SIGNATURE	DATE
DRAWN	LC	L.Crane	23/10/2020
CHECKED	-	-	-
APPROVED	-		-

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS SURFACE FINISH: MDPE TOLERANCES: ±3%	 3RD ANGLE PROJECTION
---	--------------------------

DO NOT SCALE DRAWING	REVISION: -
----------------------	-------------

ENDURAMAXX® FLUID MANAGEMENT INNOVATION

TITLE: 1500L 30DEG Cone tank - slider setup
--

DWG NO: 102242-HTEX1.5K60DEG	A3
-------------------------------------	----

SCALE:1:25	SHEET 1 OF 1
------------	--------------